

Overzicht Até remvloeistoffen:



						
	Até G	Até SL DOT4	Até SL6 DOT4	Até Super DOT 4	Até Super DOT 5.1	Até TYPE 200
				Uitlopend.		Vervanger van de "Racing Blue"
Op basis van:	Glycol	Glycol	Glycol	Glycol	Glycol	Glycol
Type:	DOT 3	DOT 4	DOT 4 ISO Klasse 6	DOT 4	DOT 5.1	DOT 4
Droogkookpunt:	245° C	260° C	265° C	260° C	265° C	280° C
Natkookpunt:	150° C	165° C	175° C	180° C	180° C	198° C
Viscositeit bij -40° C.	max. 1500 mm ² /s	max. 1400 mm ² /s	max. 700 mm ² /s	max. 1400 mm ² /s	max. 750 mm ² /s	max. 1400 mm ² /s
Bijzonderheden:	De traditioneel gebruikte remvloeistof voor oude auto's.	Normale standaard Dot 4 remvloeistof. Goede kwaliteit.	Lage viscositeit. Hoge kwaliteit.	Alleen volgens voertuigvoorschrift.	Lage viscositeit. Speciaal voor ABS, ESP en ASR. Uitermate geschikt voor zowel warme als koude toepassingen door 5° C hoger natkookpunt.	Minimale kookpuntverlaging dankzij uitstekend waterbindingsvermogen.
Verversingsinterval:	Tot 1 jaar.	Tot 1 jaar.	Tot 2 jaar.	Tot 2 jaar.	Tot 3 jaar.	Tot 3 jaar.
0,25 ltr. blik	-	-	AT 706408	-	-	-
0,5 ltr. blik	-	-	-	-	-	-
1 ltr. blik	AT 705302	AT 705802	AT 706402	-	AT 706602	AT 706202
5 ltr. blik	AT 705303	AT 705803	AT 706403	AT 706003	AT 706603	AT 706203
20 ltr. blik	-	AT 705811	AT 706411	-	AT 706611	-
30 ltr. blik	-	AT 705820	AT 706420	AT 706020	-	AT 706220
50 ltr. blik	-	AT 705814	AT 706414	-	-	AT 706214
200 ltr. vat	-	AT 705805	AT 706415	AT 706005	-	AT 706205

Opmerking: Até levert geen remvloeistof op basis van silicone.

TvH2021-03